

LUNA BL



Integrated

Reflector with integrated LED unit

Durable

Impact-resistant polycarbonate casing (IK08)

HOUSING Polycarbonate, impact-resistant, IK08.

LAMP COVER Polycarbonate with integrated LED unit.

SEALS Age-resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

ASSEMBLY Variable mounting distances with PRACHT-CLIP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.




FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 fluorescent light-exchange.

Individual luminaire, color temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x22 W	120° wide	2800 lm	5211004	1200 mm	1,8 kg
1x43 W	120° wide	5400 lm	5211014	1200 mm	1,8 kg
1x31 W	120° wide	3800 lm	5211005	1500 mm	2,1 kg
1x52 W	120° wide	6500 lm	5211015	1500 mm	2,1 kg

ACCESSORIES

Through-wiring	P/N
3x1,5mm² Set LUNA BL 1,2m, consisting of rigid cable, Terminalblock one-sided	5552132
3x1,5mm² Set LUNA BL 1,5m, consisting of rigid cable, Terminalblock one-sided	5552135
5x2,5mm² Set LUNA BL 1,2m, consisting of rigid cable, Terminalblock one-sided	5552152
5x2,5mm² Set LUNA BL 1,5m, consisting of rigid cable, Terminalblock one-sided	5552155

   **Protection class I according to EN 60598**
Protection type IP65
AC 220-240 V 50/60 Hz *registered



Solid

High-quality stainless steel clips

Easy Fix

Extremely fast assembly

ALLROUNDER

EXTREMELY FAST ASSEMBLY
DIFFUSER LUMINAIRE
HIGH QUALITY ENEC
PRICE / PERFORMANCE
DUST-TIGHT HOMOGENEOUS LIGHT
1:1 REPLACEMENT

3

YEAR WARRANTY



50.000 h LIFETIME



A++

IP65



-20°C ... +35°C

PRACHT.COM

+49 64 66 / 91 40 - 0